


Atios DALI-2 Button Coupler AFD-B4 Datasheet



TECHNICAL SPECIFICATIONS

DALI control device	DALI-2 Multimaster
Power consumption	<2 mA, supplied via DALI bus
Number of DALI-2 addresses	1, can be assigned by DALI application controller
Input number	4 potential-free inputs
Input for	Buttons, switches, motion detectors, etc.
Max. wire length	200 m
DALI standard	DALI-2 certified, complies with IEC 62386-101, IEC 62386-103, IEC 62386-301
DALI-2 events	Button pressed, released, short press, double press, long press start/stop
Dimensions	40.5 × 28 × 14.5 mm, in-wall device, for flush mount installation
Ambient temperature	-5 °C to +45 °C (operation), -25 °C to +55 °C (storage)
Certifications	CE, RoHS, DALI-2 certified, ISO 9001:2015

APPLICATION AREA AND FEATURES

- DALI-2 control device that integrates existing push switches into a DALI system.
- Four DALI-2 pushbutton instances are available for easy integration.
- Suitable for integration and in combination with DALI-2 compliant central control units.
- DALI-2 events: button pressed, released, short press, double press, long press start/stop.
- Compact in-wall device for flush mount installation behind any standard switch.
- Powered directly via the DALI bus, no additional power supply required.

